



**WAMCO** POLISHED ROD  
SPACER SYSTEM

### Wamco Suitcase Recommended Procedures:

The Wamco Suitcase is designed, engineered and manufactured, using high quality materials.

The Wamco Suitcase is a tool used to support the rod string, while re-spacing the downhole pump to enhance production, during the tagging of the downhole pump, the change out of a load cell or any adjustment to pump positioning.



As pictured above, the Suitcase consists of a bottom adapter plate, 12 or 18" Suitcase Spacer and a top adapter plate. Adapter plates have either a 1 ½ inch or 1 ¾ inch opening. The 1 ½ inch plates are blue, while the 1 ¾ inch plates are red. Spacers are sized for 1 ¼, 1 ½ and 1 ¾ inch rods. The 1 ¾ inch Spacer may be used for all rod sizes, when being used as part of a Suitcase.

- The bottom adapter plate rests on the stuffing box on the wellhead – the welded ring must be in the up position.
- The height of the Suitcase should be at least 3 – 4" higher than the Spacer(s), or other equipment to be removed from above the Carrier Bar.
- After removing the detent pin(s), the Spacer(s) are then placed on the adapter plate with the Spacer opening at 180 degrees to the opening in the plate.
- Re-insert the detent pin(s) fully into the Spacer(s).
- The top adapter plate is then placed on top of the Spacer(s), welded ring in the "down" position. This adapter plate should most closely fit the rod string, by using either the 1 ½ or 1 ¾ inch adapter plate.

After fastening a rod clamp above the Suitcase, the Suitcase will support the Rod String. Visual inspections should be carried out prior to each use.

[www.wamcorodspacers.com](http://www.wamcorodspacers.com)

Toll Free Ph. 1-800-667-7930

[sales@wamcorodspacers.com](mailto:sales@wamcorodspacers.com)

#### DISTRIBUTERS

*MRC Global      West Central Compressors*

*Distribution Now*

*Wolseley Industria*

*Baron Oilfield*

*Apex Distribution*